

ASRelay 3500 folder inserter

Productivity and confidence built in.

Eliminate the time-consuming task of folding and inserting your mail with the ASRelay 3500 folder inserter. Our simple user experience is designed on a tried and tested platform that enables you to finish up to 20,000 mail pieces per month.

With accuracy and reliability built in, your team gains confidence knowing that your critical mail is getting out the door accurately on time, every time, without errors.

The ASRelay 3500 folder inserter provides simple, accurate and reliable mail assembly.



Simplicity

Thoughtfully designed for any user.



Accuracy

Eliminate costly delays due to manual errors.



Productivity

Keep mail process moving with fast, uninterrupted performance



Specifications for Relay 3500

| | |
|----------------------------|---|
| System | ASRelay 3500 |
| Cycle speed | 3,000 per hour |
| Colour touchscreen UI | Standard |
| Monthly capacity | Up to 20,000/month |
| Feeder configuration | 2 Sheet feeders, 1 insert feeder, outer envelope feeder |
| Fold options | C, Z, Half (V), Double |
| Integrity options | OMR, 2D |
| Cascade from sheet feeders | Yes |
| Envelope sealing | Standard |

Accumulate before folding

| | |
|------------------------------|----------------------------------|
| C or Z fold | up to 5 sheets* |
| Half fold | up to 10 sheets (2 groups of 5)* |
| Double Fold (US Legal Paper) | up to 3 sheets* |

Sheet Feeder Tray(s)

| | |
|-------------------|---|
| Capacity per tray | 325 sheets 75 gsm/20 lb paper (650 sheets total) |
| Paper sizes | Minimum: 178 mm (7") Width x 178 mm (7") Length Maximum: 229 mm (9") Width x 406 mm (16") Length |
| Paper weights | Minimum: 75 gsm/20 lb Maximum: 120 gsm/32lb |

Insert Feeder Tray

| | |
|---------------|--|
| Capacity | 300 |
| Media sizes | Minimum: 127 mm (5") Width x 82 mm (3.25") Length Maximum: 230 mm (9") Width x 152 mm (6") Length |
| Media weights | Minimum: 75 gsm/20 lb (non-folded cut sheet), 60 gsm/16 lb (folded material) Maximum: 180 gsm/50 lb (single sheet) maximum compressed thickness of 2 mm (.078") |



Envelope specifications

| | |
|-------------------|---|
| Capacity | up to 100 |
| Envelope Sizes | Minimum: 88 mm (3.5") Deep x 220 mm (8.5") Wide Maximum: 164 mm (6.5") Deep x 242 mm (9.5") Wide |
| Envelope weights | Minimum: 65 gsm (17 lb) Maximum: 100 gsm (26 lb) |
| Programmable jobs | 20 |

Physical specifications

| | |
|---------------------------|---|
| Tabletop Dimensions | 711 mm L x 533 mm W x 635 mm H (28" x 21" x 25") |
| Full Installed dimensions | 1067 mm L x 533 mm W x 635 mm H (42" x 21" x 25") |
| Weight | 66 kg (145 lb) |

Accessory Physical specifications

| | |
|---|--|
|  | Vertical Power Stacker |
| | Installed Length: 356 mm/14 inches Height: 610 mm/24 inches |
|  | Drop Stacker |
| | Installed Length: 267 mm/10.5 inches |

*Based on 75 gsm/20 lb



Ashcroft Mailing Solutions Limited
Kinwarton House
Captain's Hill
Alcester
Warwickshire B49 6HA

0800 458 2880
info@ashcroftmailing.co.uk